




PRODUCT INFORMATION

- Demountable partition
- Double glazed and single glazed system
- 100mm aluminium framework
- Numerous door options
- Manufactured in Spiralis' factory in Italy
- ± 15mm deflection head


ACOUSTIC INFORMATION

- Able to achieve RW50db using 12.8mm acoustic laminated glass
- Vacuum sealed pivot door achieves RW36db




DOUBLE GLAZED PARTITION

10mm + 10mmm toughened glass





MULLION PARTITION

100mm mullion



VACUUM SEALED DOOR





PRODUCT OVERVIEW

P100 SYSTEM

Head channel details

Double glazed and single glazed

Finish: Standard aluminium anodised (can come in different finishes

upon request)

Size: 100mm x 78mm

Finish: Standard aluminium anodised (can come in different finishes

upon request)

Size: 100mm x 78mm

Deflection head

 \longrightarrow ± 15 mm deflection hea

Glass thickness -----

Single glazed and double glazed glass can come in either 10mm or 12mm clear float toughened or low iron toughened. For acoustic

Door types

Double glazed sliding door
 Single glazed centred door

Vacuum acaled dauble glaze

Vacuum sealed double glazed door Single and double glazed pivot door Timber door 44mm or 54mm

Glass sizes

As standard module sizes we work between 200mm and 1200mm.

Maximum height is 3000mm. For further glass sizes, please speak to our technical department. (Please note that some sizes are subject to the building configuration and access to the building)

Acquetic ratings

Double glazed:

Rw 50db 10.8mm + 12.8mm laminated glass Rw 45db 10mm + 12mm toughened glass

For our certificates please go to our site

